



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/645,807	08/21/2003	Wen-Pin Lin	LIN 5-1/2100.001000	8034
46290	7590	09/26/2007		
WILLIAMS, MORGAN & AMERSON 10333 RICHMOND, SUITE 1100 HOUSTON, TX 77042			EXAMINER NGUYEN, TUAN HOANG	
			ART UNIT 2618	PAPER NUMBER
			MAIL DATE 09/26/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/645,807

Applicant(s)

LIN ET AL.

Examiner

Tuan H. Nguyen

Art Unit

2618

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 15 June 2007.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-31 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-31 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed on 06/15/2007 have been fully considered but they are not persuasive.

In response to Applicant's remark on pages 10-11, Applicant argues that Kiang et al. (US PAT. 6,453,151 hereinafter "Kiang") reference cited by the Examiner does not teach measuring a power level of a signal provided by the transmitting component in response to receiving the request from the remote unit. Examiner respectfully disagrees with the Applicant argument. Applicant should refer to Kiang reference (col. 4 lines 50-65) where as the Examiner interpreted in establishing the communication link, BSC 102 (transmitting component) requests that MS 106 (remote unit) measure the signal strength received using the, always present, known pilot bits transmitted in pilot channel 201. MS 106 measures the received signal strength by using the amplitude values of the pilot bits and returns this measured value to the base station controller. Therefore, the teaching of the prior art references still read on.

Base on the above rational, it is believed that the claimed limitations are met by the references submitted and therefore, the rejection maintained.

Claim Rejections - 35 USC § 102

Art Unit: 2618

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1-5, 11, 17, and 31 are rejected under 35 U.S.C. 102(b) as being anticipated by Kiang et al. (US PAT. 6,453,151 hereinafter "Kiang").

Consider claim 1, Kiang teaches receiving a request from a remote unit (106) to provide a power level associated with a transmitting component (102), wherein the request is transmitted over a communications protocol (fig. 1 col. 4 line 50 through col. 5 line 8); measuring a power level of a signal provided by the transmitting component in response to receiving the request from the remote unit (fig. 1 col. 4 line 5 through col. 5 line 3); and providing the measured power level to the remote unit over the communications protocol (fig. 1 col. 4 line 65 through col. 5 line 3).

Consider claim 2, Kiang further teaches determining if the measured power level is within an acceptable range (fig. 3 col. 6 lines 14-28).

Consider claim 3, Kiang further teaches receiving a request from the remote unit to adjust a power level of an output signal provided by the transmitting component in response to determining that the measured power level is outside the acceptable range

Art Unit: 2618

(col. 6 lines 7-13).

Consider claim 4, Kiang further teaches adjusting the power level of an output signal provided by the transmitting component in response to determining that the measured power level is outside the acceptable range (col. 6 lines 7-13).

Consider claim 5, Kiang further teaches adjusting the power level comprises attenuating the output signal provided by the transmitting component by a preselected amount in response to determining that the measured power level is higher than desired (col. 6 lines 7-13).

Consider claim 11, Kiang teaches an article comprising one or more machine-readable storage media containing instructions that when executed enable a processor to: receive a request from a remote unit to indicate a power level of a signal provided by a transmitting component (fig. 1 col. 4 line 50 through col. 5 line 8); determine a power level of the signal in response to receiving the request from the remote unit (fig. 1 col. 4 line 5 through col. 5 line 3); determine if the measured power level is at an acceptable level (fig. 3 col. 6 lines 14-28); and adjust a power level of an output signal provided by the transmitting component by a preselected level in response to determining that the measured power level is not at the acceptable level (fig. 3 col. 6 lines 7-13).

Consider claim 17, Kiang teaches an interface adapted to receive a request from a remote unit (106) to adjust a transmit power level of a first component (102) of a base station (fig. 1 col. 4 line 50 through col. 5 line 8); and a control unit communicatively coupled to the interface, the control unit adapted to: determine a power level of an output signal of the first component in response to the request (fig. 3 col. 6 lines 14-28); and provide the determined power level of the output signal of the first component to the remote unit (fig. 1 col. 4 line 5 through col. 5 line 3).

Consider claim 31, Kiang teaches means for receiving a request from a remote unit to provide a power level associated with a transmitting component, wherein the request is transmitted over a communications protocol (page 9 [0122]); means for measuring a power level of a signal provided by the transmitting component in response to receiving the request from the remote unit (fig. 1 col. 4 line 5 through col. 5 line 3); and means for providing the measured power level to the remote unit over the communications protocol (col. 4 line 59 through col. 5 line 8).

Claim Rejections - 35 USC § 103

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

5. Claims 6, 8 and 18-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Schulist et al. (U.S PUB. 2006/0018289 hereinafter "Schulist").

Consider claim 6, Kiang teaches adjusting the power level of an output signal provided by the transmitting component in response to determining that the measured power level is outside the acceptable range.

Kiang does not explicitly show that adjusting the power level comprises decreasing an amount of attenuation applied to the output signal provided by the transmitting component by a preselected amount in response to determining that the measured power level is lower than desired.

In the same field of endeavor, Schulist teaches adjusting the power level comprises decreasing an amount of attenuation applied to the output signal provided by the transmitting component by a preselected amount in response to determining that the measured power level is lower than desired (page 6 [0073]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, adjusting the power level comprises decreasing an amount of attenuation applied to the output signal provided by the transmitting component by a preselected amount in response to determining that the measured power level is lower than desired, as taught by Schulist, in order to control access to a

Art Unit: 2618

node of a wireless communications network in which identification codes are used to differentiate access requests of different network components.

Consider claim 8, Schulist further teaches the transmitting component is a baseband radio, and wherein measuring the power level comprises measuring the power level of at least one of a paging channel, synchronization channel, access channel, traffic channel, and pilot channel (page 5 [0067]).

Consider claim 18, Kiang further teaches the base station services a cellular communications system and wherein the output signal comprises at least one of a paging channel, synchronization signal, traffic channel, access channel, and pilot channel, and wherein the control unit is further adapted to determine if the measured power level is at an acceptable level (page 5 [0067]).

Consider claim 19, Kiang further teaches the control is further adapted to adjust a power level of an output signal provided by the transmitting component by a preselected level in response to determining that the measured power level is not at the acceptable level (col. 6 lines 7-13).

Consider claim 20, Kiang further teaches the control unit is adapted to adjust the power level by adjusting an amount of attenuation that is applied to the output signal (col. 6 lines 7-13).

6. Claims 7 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Burchfiel (U.S. PUB. 2004/0092281).

Consider claim 7, Kiang teaches receiving a request from a remote unit to provide a power level associated with a transmitting component, wherein the request is transmitted over a communications protocol; measuring a power level of a signal provided by the transmitting component in response to receiving the request from the remote unit; and providing the measured power level to the remote unit over the communications protocol.

Kiang does not explicitly show that the transmitting component is a baseband radio and wherein signal provided by the baseband radio is deliverable to one of an antenna port and a power meter, and wherein measuring the power level comprises directing the signal provided by the baseband radio to the power meter in response to receiving the request from the remote unit.

In the same field of endeavor, Burchfiel teaches the transmitting component is a baseband radio and wherein signal provided by the baseband radio is deliverable to one of an antenna port and a power meter, and wherein measuring the power level comprises directing the signal provided by the baseband radio to the power meter in response to receiving the request from the remote unit (page 12 [0153]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, the transmitting component is a baseband radio

Art Unit: 2618

and wherein signal provided by the baseband radio is deliverable to one of an antenna port and a power meter, and wherein measuring the power level comprises directing the signal provided by the baseband radio to the power meter in response to receiving the request from the remote unit, as taught by Burchfiel, in order to increase the available spectrum in a wireless network.

Consider claim 16, Burchfiel further teaches the transmitting component is a baseband radio and wherein a signal provided by the baseband radio is deliverable to one of an antenna port and a power meter, wherein the instructions when executed enable the processor to direct the signal provided by the baseband radio to the power meter in response to receiving the request from the remote unit (page 12 [0153]).

7. Claims 9 and 14-15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Evans et al. (U.S. PUB. 2004/0257988 hereinafter "Evans").

Consider claim 9, Kiang teaches receiving a request from a remote unit to provide a power level associated with a transmitting component, wherein the request is transmitted over a communications protocol; measuring a power level of a signal provided by the transmitting component in response to receiving the request from the remote unit; and providing the measured power level to the remote unit over the communications protocol.

Kiang does not explicitly show that the communications protocol is a high-level data link control protocol, wherein the transmitting component is associated with a base station of a cellular communications system, and wherein the remote unit is located in a mobile services switching center associated with the base station.

In the same field of endeavor, Evans teaches the communications protocol is a high-level data link control protocol, wherein the transmitting component is associated with a base station of a cellular communications system, and wherein the remote unit is located in a mobile services switching center associated with the base station (pages 3 and 4 [0038]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, the communications protocol is a high-level data link control protocol, wherein the transmitting component is associated with a base station of a cellular communications system, and wherein the remote unit is located in a mobile services switching center associated with the base station, as taught by Evans, in order to provide a data transmission system for determining whether to allow transmission of data, the data transmission system comprising: a source for transmitting data destined for a destination over a network.

Consider claim 14, Evans further teaches the transmitting component is associated with a base station of a cellular communications system, wherein the instructions when executed enable the processor to receive the request over a communications protocol from a mobile services switching station associated with the

Art Unit: 2618

base station (pages 3 and 4 [0038]).

Consider claim 15, Evans further teaches the instructions when executed enable the processor to provide the measured power level to the remote unit located at the mobile services switching center (pages 3 and 4 [0038]).

8. Claim 10 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Evans, and further in view of Mortazavi et al. (U.S PUB. 2002/0188764 hereinafter "Mortazavi").

Consider claim 10, Kiang and Evans in combination, fails to teaches the base station comprises at least a second transmitting component, wherein measuring the power level comprises deactivating the second transmitting component before measuring the power level.

However, Mortazavi teaches the base station comprises at least a second transmitting component, wherein measuring the power level comprises deactivating the second transmitting component before measuring the power level (page 2 [0016]).

Therefore, it is obvious to one of ordinary skill in the art at the time the invention was made to incorporate the disclosing of Mortazavi into view of Kiang and Evans, in order to provide an exception handler allowing asynchronous invocation of remote objects.

9. Claims 12-13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang as applied to claim 11 above, and further in view of Kobayashi et al. (U.S. PAT. 5,574,993 hereinafter "Kobayashi").

Consider claim 12, Kiang teaches an article comprising one or more machine-readable storage media containing instructions that when executed enable a processor to: receive a request from a remote unit to indicate a power level of a signal provided by a transmitting component; determine a power level of the signal in response to receiving the request from the remote unit; determine if the measured power level is at an acceptable level; and adjust a power level of an output signal provided by the transmitting component by a preselected level in response to determining that the measured power level is not at the acceptable level.

Kiang does not explicitly show that the instructions when executed enable the processor to decrease the power of the output signal by attenuating the output signal by a preselected amount.

In the same field of endeavor, Kobayashi teaches the instructions when executed enable the processor to decrease the power of the output signal by attenuating the output signal by a preselected amount (col. 9 lines 19-32).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, the instructions when executed enable the processor to increase the power of the output signal by decreasing an amount of attenuation that is applied to the output signal, as taught by Kobayashi, in order to

provide a mobile communication which is capable of maintaining the linearity during a small power output similar to the linearity during a large power output for a radio-frequency power.

Consider claim 13, Kiang further teaches the instructions when executed enable the processor to decrease the power of the output signal by attenuating the output signal by a preselected amount (col. 9 lines 19-54).

10. Claims 21-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Nakayama (U.S PUB. 2004/0180686).

Consider claim 21, Kiang teaches an interface adapted to receive a request from a remote unit to adjust a transmit power level of a first component of a base station; and a control unit communicatively coupled to the interface, the control unit adapted to: determine a power level of an output signal of the first component in response to the request; and provide the determined power level of the output signal of the first component to the remote unit.

Kiang does not explicitly show that a power meter, wherein the control unit is adapted to provide the output signal of the first component to the power meter.

In the same field of endeavor, Nakayama teaches a power meter, wherein the control unit is adapted to provide the output signal of the first component to the power meter (page 2 [0026]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, a power meter, wherein the control unit is adapted to provide the output signal of the first component to the power meter, as taught by Nakayama, in order to provide a transmission output circuit can always perform correct transmission power control, and can detect the abnormality of transmission power.

Consider claim 22, Nakayama further teaches a switch device adapted to receive the output signal from the first component and adapted to provide the output signal to at least one of an antenna port and the power meter in response to receiving a signal from the control unit (page 6 [0087]).

11. Claim 23 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Mortazavi et al. (U.S. PUB. 2002/0188764 hereinafter "Mortazavi").

Consider claim 23, Kiang teaches an interface adapted to receive a request from a remote unit to adjust a transmit power level of a first component of a base station; and a control unit communicatively coupled to the interface, the control unit adapted to: determine a power level of an output signal of the first component in response to the request; and provide the determined power level of the output signal of the first component to the remote unit.

Kiang does not explicitly show that the base station comprises a second component, and wherein the control unit is adapted to deactivate the second

Art Unit: 2618

component of the base station before determining the power level of the output signal of the first component.

In the same field of endeavor, Mortazavi teaches the base station comprises a second component, and wherein the control unit is adapted to deactivate the second component of the base station before determining the power level of the output signal of the first component (page 2 [0026]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, the base station comprises a second component, and wherein the control unit is adapted to deactivate the second component of the base station before determining the power level of the output signal of the first component, as taught by Mortazavi, in order to provide an exception handler allowing asynchronous invocation of remote objects.

12. Claim 24 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Mortazavi, and further in view of Kim (U.S PAT. 6,701,136).

Consider claim 24, Kiang and Mortazavi in combination, fails to teaches the first component is a baseband radio associated with an alpha sector of a first carrier and the second component is a baseband radio associated with the alpha sector of a second carrier.

However, Kim teaches the first component is a baseband radio associated with an alpha sector of a first carrier and the second component is a baseband radio associated with the alpha sector of a second carrier (see fig. 1 col. 2 lines 20-22).

Therefore, it is obvious to one of ordinary skill in the art at the time the invention was made to incorporate the disclosing of Kim into view of Kiang and Mortazavi, in order to detection and setting of the optimal transmission attenuation values for multiple CDMA channels, thereby reducing time and cost for the detection and setting.

13. Claims 25 and 30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Benveniste (U.S. PUB. 2003/0064745).

Consider claim 25, Kiang teaches a communications system, comprising: a base station communicatively coupled to the remote unit over a communications protocol, the base station adapted to: receive the request; measure a power level of a signal provided by a transmitting component (fig. 1 col. 4 line 50 through col. 5 line 8 e.g., in establishing the communication link, Base Station Controllers (BSC) 102 requests that Mobile Stations (MS) 106 measure the signal strength received using the pilot bits transmitted in pilot channel 201. MS 106 measures the received signal strength by using the amplitude values of the pilot bits and returns this measured value to the base station controller. BSC 102, considering the capacity of the base station and other users within the system, uses the measured signal strength (read on power level) to assign the transmission parameters such as transmission data rate, bandwidth, and, nominal

Art Unit: 2618

initial output power to provide an acceptable quality of service to MS 106); determine if the measured power level is at an acceptable level (fig. 3 col. 6 lines 14-28 e.g., the nominal output power level, level 320a, is typically chosen to be sufficiently high to insure an acceptable quality of service (read on acceptable range) at the limits of the transmitter's coverage area. With the transmission parameters established, the transmitter then begins transmission of data traffic to MS 106. MS 106, in receiving the data traffic, determines signal parameters, such as received signal strength); and adjust a power level of an output signal provided by the transmitting component by a preselected level in response to determining that the measured power level is not at the acceptable level (fig. 3 col. 6 lines 7-13 e.g., MS 106, continue this interactive message exchange whereby the transmitter continues to reduce (read on adjust) the output power to output power levels 320c, 320d, 320e in response to the autonomously transmitted messages 330b, 330c, 330d, respectively. However, continued reduction of the output power can result in output power levels that are too low (compared to preselect power level) for acceptable service (read on power is not at the acceptable level)).

Kiang does not explicitly show that a remote unit adapted to provide a request to calibrate a transmit power level.

In the same field of endeavor, Benveniste teaches a remote unit adapted to provide a request to calibrate a transmit power level (page 10 [0163]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use, a remote unit adapted to provide a request to

Art Unit: 2618

calibrate a transmit power level, as taught by Benveniste, in order to provide RF transmit power levels are self calibrated by using data collected by the wireless system determined by system functionalities as part of the self-configuration process.

Consider claim 30, Kiang further teaches the base station is associated with at least one of a local area network and a cordless communications system (col. 3 lines 7-12).

14. Claims 26-27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Benveniste, and further in view of Kim (U.S PAT. 6,701,136).

Consider claim 26, Kiang and Benveniste, in combination, fails to teaches the base station is a base station for a cellular communications system.

However, Kim teaches the base station is a base station for a cellular communications system (col. 1 line 45 through col. 2 line 15).

Therefore, it is obvious to one of ordinary skill in the art at the time the invention was made to incorporate the disclosing of Kim into view of Kiang and Benveniste, in order to detection and setting of the optimal transmission attenuation values for multiple CDMA channels, thereby reducing time and cost for the detection and setting.

Consider claim 27, Kim further teaches the base station is adapted to provide a three-carrier, three-sector coverage (see fig. 1 col. 2 lines 20-22).

15. Claim 28 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Benveniste and Kim, and further in view of Rath (U.S. PUB. 2005/0068902).

Consider claim 28, Kiang, Benveniste, and Kim in combination, fails to teaches the base station is adapted to provide a six-carrier, six-sector coverage.

However, Rath teaches the base station is adapted to provide a six-carrier, six-sector coverage (see fig. 2 page 2 [0040] and page 3 [0051]).

Therefore, it is obvious to one of ordinary skill in the art at the time the invention was made to incorporate the disclosing of Rath into view of Kiang, Benveniste, and Kim, in order to provide a combination of high data rates to a large number of users and >99% coverage to potential customers in a service area.

16. Claim 29 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kiang in view of Benveniste as applied to claim 25 above, and further in view of Evans et al. (U.S. PUB. 2004/0257988 hereinafter "Evans").

Consider claim 29, Kiang and Benveniste, in combination, fails to teaches the remote unit is located at a mobile services switching center associated with the base station.

However, Evans teaches the remote unit is located at a mobile services switching center associated with the base station (pages 3 and 4 [0038]).

Art Unit: 2618

Therefore, it is obvious to one of ordinary skill in the art at the time the invention was made to incorporate the disclosing of Evans into view of Kiang and Benveniste, in order to provide a data transmission system for determining whether to allow transmission of data, the data transmission system comprising: a source for transmitting data destined for a destination over a network.

Conclusion

17. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

18. Any response to this action should be mailed to:

Mail Stop _____ (Explanation, e.g., Amendment or After-final, etc.)

Commissioner for Patents

Art Unit: 2618

P.O. Box 1450

Alexandria, VA 22313-1450

Facsimile responses should be faxed to:

(571) 273-8300

Hand-delivered responses should be brought to:

Customer Service Window

Randolph Building

401 Dulany Street

Alexandria, VA 22313

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tuan H. Nguyen whose telephone number is (571) 272-8329. The examiner can normally be reached on 8:00Am - 5:00Pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Maung Nay A. can be reached on (571)272-7882882. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Art Unit: 2618

Information Consider the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Tuan Nguyen
Examiner
Art Unit 2618

TN


NAY MAUNG
SUPERVISORY PATENT EXAMINER